

SAFETY DATA SHEET

Topical Hand Rub

Date of Preparation: April 21, 2020

Section 1: IDENTIFICATION

Product Name: Topical Hand Rub

Natural Product Number (NPN): 80098297.

Product Use: Hand Sanitizer.

Restrictions on Use: Not available.

Manufacturer/Supplier: 62 Degrees North Inc.

PO Box 2896 Stn Main Yellowknife, NT X1A 2R2

Phone Number: 1-867-446-7883

Emergency Phone: CANUTEC: 1-888-CAN-UTEC (226-8832), 613-996-6666 or

*666 on a cellular phone.

Date of Preparation of SDS: April 21, 2020

Section 2: HAZARD(S) IDENTIFICATION

GHS INFORMATION

This GHS classification listed below is written for bulk handling and not personal use. For personal use, please follow the directions on the packaging. This SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large spills.

Classification: Flammable Liquids, Category 2

Eye Irritation, Category 2A

Specific Target Organ Toxicity (Single Exposure), Category 3 - Narcotic Effects

LABEL ELEMENTS

Hazard

Pictogram(s):





Signal Word: Danger

Hazard Highly flammable liquid and vapor. Statements: Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical, ventilating, and lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges. Avoid breathing mist, vapours, or spray.



Date of Preparation: April 21, 2020

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing and eye protection.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor if you feel unwell.

If eye irritation persists: Get medical attention.

In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to

extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Store locked up.

Disposal: Dispose of contents and container in accordance with applicable regional,

national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: None.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

This material is considered hazardous by the Hazardous Products Regulations.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS								
Hazardous Ingredient(s)	Common name / Synonyms	CAS No.	% wt./wt.					
2-Propanol	Isopropyl alcohol	67-63-0	70 - 80					
Hydrogen peroxide (H2O2)	Hydrogen peroxide	7722-84-1	0.1 - 1					
Non-Hazardous Ingredient(s)	Common name / Synonyms	CAS No.	% wt./wt.					
Water	Not available.	7732-18-5	10 - 30					
1,2,3-Propanetriol	Glycerin	56-81-5	1 - 5					

Actual concentration range(s) withheld as a trade secret.

Section 4: FIRST-AID MEASURES

Inhalation:

If used as recommended, no first-aid measures are necessary. If handling large amounts of product and vapour is inhaled, remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If breathing or the heart stops, trained personnel should immediately begin artificial respiration (AR) or cardiopulmonary resuscitation (CPR) respectively. Get medical attention immediately.



Date of Preparation: April 21, 2020

Acute and delayed symptoms and effects: Normal use is not expected to cause any adverse effects. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness.

Eye Contact: If in eyes: Rinse cautiously with water for at least 20 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical attention.

Acute and delayed symptoms and effects: Causes serious eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred

or hazy vision. Isopropanol may cause transient corneal injury.

Skin Contact: If used as recommended, no first-aid measures are necessary. If in

contact with large amounts of product: Rinse skin with water or shower.

Call a poison center or doctor if you feel unwell.

Acute and delayed symptoms and effects: No adverse effects are expected under normal conditions of use. Handling of large amounts may cause

skin dryness and/or irritation.

Ingestion: If swallowed: Call a poison center or doctor if you feel unwell. If vomiting

occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If breathing or the heart stops, trained personnel should immediately begin artificial respiration (AR) or cardiopulmonary resuscitation (CPR) respectively. Get

medical attention immediately.

Acute and delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset,

nausea, vomiting and diarrhea.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately. For Isopropanol intoxication, a

urine acetone test may be helpful in diagnosis. Hemodialysis should be

considered in severe cases.

Section 5: FIRE-FIGHTING MEASURES

FLAMMABILITY AND EXPLOSION INFORMATION

Highly flammable liquid and vapor. Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Liquid is lighter than water.

If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.



SAFETY DATA SHEET

Topical Hand Rub

Date of Preparation: April 21, 2020

Fire involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

Sensitivity to Mechanical Impact: This material is not sensitive to mechanical impact. Sensitivity to Static Discharge:

Take action to prevent static discharges. This material is

sensitive to static discharge.

MEANS OF EXTINCTION Suitable Extinguishing Media:

Small Fire: Dry chemical, CO2, water spray or alcohol-

resistant foam.

Large Fire: Water spray, fog or alcohol-resistant foam. Move

containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media: Do not use straight streams. CAUTION: This product has a

very low flash point: Use of water spray when fighting fire

may be inefficient.

Products of Combustion: Oxides of carbon. Acrolein.

Protection of Firefighters: Inhalation or contact with material may irritate or burn skin

> and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited

protection.

Section 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area

> for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in

immediate area). All equipment used when handling the product

must be grounded.

Personal Precautions: Do not touch or walk through spilled material. Use personal

protection recommended in Section 8.

Environmental Precautions: Prevent entry into waterways, sewers, basements or confined

areas.

Methods for Containment: Stop leak if you can do it without risk. A vapor suppressing foam

may be used to reduce vapors.



Date of Preparation: April 21, 2020

Methods for Clean-Up: Absorb or cover with dry earth, sand or other non-combustible

material and transfer to containers. Use clean non-sparking tools

to collect absorbed material.

Other Information: See Section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE

Handling:

Do not swallow. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist, vapours, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. See Section 8 for information on Personal Protective Equipment.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines Component

Isopropyl alcohol [CAS No. 67-63-0]

ACGIH: 200 ppm (TWA); 400 ppm (STEL); A4; BEI (2001)

OSHA: 400 ppm (TWA), 980 mg/m³ (TWA);

500 ppm (STEL) [Vacated];

Hydrogen peroxide [CAS No. 7722-84-1]

ACGIH: 1 ppm (TWA); A3 (1990)

OSHA: 1 ppm (TWA), 1.4 mg/m³ (TWA);

Water [CAS No. 7732-18-5]

ACGIH: No TLV established. **OSHA:** No PEL established.

Glycerin [CAS No. 56-81-5]

ACGIH: No TLV established.

OSHA: 15 mg/m³ (Total particulate) (TWA), 5 mg/m³ (Respirable fraction) (TWA);

10 mg/m³ (Total particulate) (TWA) [Vacated]:

PEL: Permissible Exposure Limit TLV: Threshold Limit Value TWA: Time-Weighted Average STEL: Short-Term Exposure Limit

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels

of dust, fume, vapour, gas, etc.) below recommended exposure limits. Use explosion-proof electrical, ventilating,

and lighting equipment.



SAFETY DATA SHEET

Topical Hand Rub

Date of Preparation: April 21, 2020

PERSONAL PROTECTIVE EQUIPMENT (PPE)



Eye/Face Protection: Wear chemical safety goggles when handling large amounts

of product. Ensure that eyewash stations are close to the workstation location. Use equipment for eye protection that

meets the standards referenced by CSA Standard CAN/CSA-Z94.3-92 and OSHA regulations in 29 CFR

1910.133 for Personal Protective Equipment.

Hand Protection: Wear protective gloves when handling large amounts of

product. Consult manufacturer specifications for further

information.

Skin and Body Protection: Wear protective clothing when handling large amounts of

product. Flame resistant clothing that meets the NFPA 2112 and CAN/CGSB 155.20 standards is recommended in areas

where material is stored or handled.

Respiratory Protection: Not necessary under normal conditions of use. If handling

large amounts of product, if engineering controls and

ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4-11, with organic vapor cartridge,

or self-contained breathing apparatus must be used.

Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed

the limits of the air-purifying respirators.

General Hygiene Considerations: Handle according to established industrial hygiene and

safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to

ensure adequate protection.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear liquid.

Colour: Colourless.

Odour: Alcohol.

Odour Threshold: Not available.

Physical State: Liquid.

pH: Not available.Melting Point / Freezing Point: Not available.



Date of Preparation: April 21, 2020

Initial Boiling Point: 83 °C (181.4 °F) (Isopropanol)

Boiling Range: Not available.

Flash Point: 11.7 °C (53.06 °F) (Closed Cup - Isopropanol)

Evaporation Rate:

Flammability (solid, gas):

Lower Flammability Limit:

Upper Flammability Limit:

Vapor Pressure:

Not available.

Not available.

Vapor Density: Not available.

Relative Density: Not available.

Solubilities: Miscible in water.

Partition Coefficient: n-

Octanol/Water:

Not available.

Auto-ignition Temperature: 456 °C (852.8 °F) (Isopropanol)

Decomposition Temperature:Not available.Viscosity:Not available.Percent Volatile, wt. %:Not available.

VOC content, wt. %: Not available.

Density: Not available.

Coefficient of Water/Oil

Distribution:

Not available.

Section 10: STABILITY AND REACTIVITY

Reactivity: Contact with incompatible materials. Sources of ignition. Exposure to

heat.

Chemical Stability: Stable under normal storage conditions.

Possibility of Hazardous

Reactions:

None known.

Conditions to Avoid: Contact with incompatible materials. Sources of ignition. Exposure to

heat.

Incompatible Materials: Acids. Strong oxidizers.

Hazardous Decomposition Products: Not available.



Date of Preparation: April 21, 2020

Section 11: TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE

Product Toxicity

Oral: Not available.

Dermal: Not available.

Inhalation: Not available.

Component Toxicity

Component CAS No. LD₅₀ oral LD₅₀ dermal LC₅₀ 3600 mg/kg Isopropyl alcohol 67-63-0 12800 mg/kg 16000 ppm (rat); 8H (mouse) (rabbit) Hydrogen 7722-84-1 376 mg/kg (rat) 4060 mg/kg (rat) 2000 mg/m³ (rat); 4H peroxide > 90000 µl/kg (rat); Water 7732-18-5 Not available. Not available. Glycerin 56-81-5 12600 mg/kg > 10000 mg/kg $> 570 \text{ mg/m}^3 \text{ (rat)}; 1H$ (rat) (rabbit)

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion. Skin absorption.

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Blood.

Kidneys. Central nervous system.

Symptoms (including delayed and immediate effects)

Inhalation: Normal use is not expected to cause any adverse effects. Excessive inhalation may

cause headache, dizziness, confusion, loss of appetite and/or loss of

consciousness.

Eye: Causes serious eye irritation. Signs/symptoms may include redness, swelling, pain,

tearing, and blurred or hazy vision. Isopropanol may cause transient corneal injury.

Skin: No adverse effects are expected under normal conditions of use. Handling of large

amounts may cause skin dryness and/or irritation.

Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain,

stomach upset, nausea, vomiting and diarrhea.

Skin Sensitization:Not available.Respiratory Sensitization:Not available.Medical ConditionsNot available.

Aggravated By Exposure:

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Blood.

Cardiovascular system. Liver. Kidneys. Reproductive system. Central

nervous system.



Date of Preparation: April 21, 2020

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation. High

vapour concentrations, generally greater than 10% by volume, may

sensitize the heart and lead to lethal cardiac arrhythmias.

Carcinogenicity: Product is not classified as a carcinogen. See Component

Carcinogenicity table below for information on individual components.

Component Carcinogenicity

ACGIH IARC Component NTP **OSHA** Prop 65 Isopropyl alcohol A4 Group 3 Not listed. Not listed. Not listed. Hydrogen peroxide А3 Group 3 Not listed. Not listed. Not listed.

Mutagenicity: Not available.

Reproductive Effects: Not available.

Developmental Effects

Teratogenicity: Not available. **Embryotoxicity:** Not available.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Not available.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Other Adverse Effects: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions: Disposal should be in accordance with applicable regional, national

and local laws and regulations. Local regulations may be more

stringent than regional or national requirements.

Section 14: TRANSPORT INFORMATION

U.S. Department of Transportation (DOT)

Proper Shipping Name: UN1219, ISOPROPANOL, 3, PG II

Class: 3

UN Number: UN1219

Packing Group: ||

Label Code:





Date of Preparation: April 21, 2020

Canada Transportation of Dangerous Goods (TDG)

Proper Shipping Name: UN1219, ISOPROPANOL, 3, PG II

Class:

UN Number: UN1219

Packing Group: ||

Label Code:



Section 15: REGULATORY INFORMATION

Chemical Inventories

US (TSCA)

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations

United States

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA Title III

Component	Section 302 (EHS) TPQ (Ibs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313	RCRA CODE	CAA 112(r) TQ (lbs.)
Isopropyl alcohol	Not listed.	Not listed.	Not listed.	313	Not listed.	Not listed.
Hydrogen peroxide	1000	1000	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

Massachusetts

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

ComponentCAS No.RTK ListIsopropyl alcohol67-63-0Listed.Hydrogen peroxide7722-84-1EGlycerin56-81-5Listed.

Note: E = Extraordinarily Hazardous Substance



Date of Preparation: April 21, 2020

New Jersey

US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated

Section 34:5A-5)

ComponentCAS No.RTK ListIsopropyl alcohol67-63-0SHHSHydrogen peroxide7722-84-1SHHSGlycerin56-81-5Listed.

Note: SHHS = Special Health Hazard Substance

Pennsylvania

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Component

CAS No.

RTK List

Isopropyl alcohol 67-63-0 E
Hydrogen peroxide 7722-84-1 E
Glycerin 56-81-5 Listed.

Note: E = Environmental Hazard

California

California Prop 65: This product does not contain chemicals known to the State of California

to cause cancer, birth defects or other reproductive harm.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

Date of Preparation of SDS: April 21, 2020

Version: 1.0

GHS SDS Prepared by: Deerfoot Consulting Inc.

Phone: (403) 720-3700